Product datasheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

APDU9953

Main

Product or component type	PDU
Main Input Voltage	200...240 V
Input current limits	32 A
Network frequency	50/60 Hz
Main Output Voltage	200...240 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
Load capacity	7400 VA
permissible voltage	220…240 V
Max current draw	32 A
Max line current	32 A
PDU type	Switched
Protection type	Circuit breaker
Number of rack unit	0U
Number of cables	1
Cable length	3 m
Provided equipment	Installation guide Rack mounting brackets Safety guide

Complementary

Mounting location	Side
Mounting mode	Not rack-mountable
Mounting position	Vertical
Communication port protocol	SNMP Redfish
Height	1829 mm
Width	56 mm
Depth	46 mm
Net weight	7.34 kg

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	VDE EAC RCM
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Relative humidity	5…95 %
Storage Relative Humidity	5…95 %
Ambient air temperature for storage	-25…65 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	204 cm
Package 1 Width	12.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	9.95 kg

Contractual warranty

Warranty (in months)	36

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**2 909 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**55 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**2 848 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**4 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**31346aed-552c-4a16-81d9-e683a383b6da**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Recyclability potential, in %	**71**
End of life manual availability	End of Life Information
Removable battery	**Yes**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative



